

4/5

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-334809

(43)Date of publication of application : 18.12.1998

(51)Int.Cl.

H01J 11/02
C03C 17/245
H01J 9/02

(21)Application number : 09-141348

(71)Applicant : FUJITSU LTD

(22)Date of filing : 30.05.1997

(72)Inventor : NAKAHARA HIROYUKI
KATAYAMA TAKASHI
IWASAKI KAZUhide
ISHIMOTO MANABU
IWASE NOBUHIRO
HIDAKA SOICHIRO
MOCHIZUKI AKIHIRO

(54) PLASMA DISPLAY PANEL AND PLASMA DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To enhance display quality by reducing the rate of occurrence of black noise that a cell to be lighted is not lighted.

SOLUTION: In a matrix display type PDP, in which the first and second electrodes composing a main pair of electrodes are coated with insulating layers with respect to a discharge gas, a magnesium oxide film which has an impedance in the range of 230-330 kΩ per square centimeter at 100 Hz, or a magnesium oxide film which contains silicon at a rate within the range of 500-10000 wt. ppm is provided as a surface layer at least contacting the discharge gas among the insulating layers.

LEGAL STATUS

[Date of request for examination] 21.08.1998

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3247632

[Date of registration] 02.11.2001

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office